

**Product Name :**  
Digital 3 Channel ECG**Product Code :**  
NMDIG10059**Description :**

Digital 3 Channel ECG 3.5" TFT screen 12 leads simultaneous display Thermal printing system Power supply both AC and DC High capacity built-in lithium rechargeable battery Battery power supports continually record 150 pieces of ECG Built-in Database Store more than 1000 pieces of archive Digital signal processor for filter Auto-measurement, auto-analysis and auto interpretation functions Lead: Standard 12 leads Patient leak current:  $\leq 50\text{M}$  Frequency response: 0.05Hz-150Hz(-3dB Time constant: Time constant  $> 3.2\text{s}$  CMRR: 100dB Dimension of recording paper: 80mm(w)x20m(L) paper Paper speed: 25mm/s, 50mm/s Sensitivity choice: 5, 10, 20mm/mV. Standard sensitivity is 10mm/mV + 0.2mm/mV Measurement parameters : HR, P-R interval, P Duration, QRS Duration, Q-T interval, Q-Tc, P Axis, QRS Axis, T Axis, R(V5), S<sub>i</sub>  $\frac{1}{2}$  (V1), R(V5)+S(V1) Product safety type: Class 1. Type CF, there is defibrillation and pacing protection circuit. Enduring polarization voltage: +300mV Noise level:  $\leq 15\mu\text{V}$  p-p Size: 315mm(L)  $\times$  215mm(W)  $\times$  77mm(H) Net Weight: 2.25Kg