

**Product Name :**  
Fully Automatic Autoclaves**Product Code :**  
NMALV10041**Description :**

Fully Automatic Autoclaves Unique plus points of NML Fully Automatic Autoclave: Pedal Free System: Pedal Free system in vertical autoclave enables you to lift the lid very easily and safely. It also reduces the loading height. This allows the user to lift the lid by only 3 to 4 mm Flexible Load Sensor: Fully Automatic Autoclaves are provided with a very unique Flexible Load Sensor which enables the user to place the load sensor anywhere in chamber. This can be placed in Flask, Petridish, Linen or any load. This enables the user to track that desired temperature is achieved in load or not. Micro Processor Controller: Unique micro processor temperature controller provides facility to programmer the cycles, with a feather touch panel Option of Fast Cooling and Slow Cooling: Our Fully Automated Autoclave provides the user option to select fast cooling or slow cooling depending on the load configuration. Robustly Built Chamber: Our Autoclaves are robustly built with latest welding technique which gives you much higher working pressure and test pressure than any other Autoclave in its category Robustly built chamber is capable of giving you working pressure of 20 PSI and test pressure of 30 PSI Unique pedal free design Lower working height Microprocessor based precise controlling User settable Multi programme cycle Flexible load sensor Data logging of 02 sensors Automatic purging, venting Low water level protection Cooling can be either fast or slow Self - diagnostic errors display IO / OQ / PQ Documentation

**Technical Specification :**

In this autoclave we provide automatic purging system through solenoid valve with automatic steam release after sterilization  
Supplied with PID Controller with timer to set time for sterilization  
Automatic release of pressure after completion of cycle with set timer  
Low water level cut of system with alarm for safety of heaters  
Specially designed heater for low power consumption  
Equipped with 2 Safety Valve, Pressure gauge on top with lid  
Max working pressure set on Valve 15 PSI with setting of controller at 121C

---

**NAUGRA<sup>®</sup>**

**Medical Hospital Equipments Manufacturers**

Website: [SITE,](#)