

Product Name :
Zoll PD 2000 Defibrillator**Product Code :**
NMCBS41001**Description :**

Zoll PD 2000 Defibrillator Tender Suppliers Africa and Zoll PD 2000 Defibrillator Manufacturers Africa Kenya, South Africa, Ivory Coast, Cameroon, Niger, Burkina Faso, Mayotte, Sao Tome, Tunisia, South Sudan, Botswana, Namibia, Gabon, Lesotho, Guinea Bissau, Equatorial Guinea, Mauritius, Eswatini, Djibouti, Reunion, Comoros, Cape Verde, Western Sahara, Mali, Malawi, Nigeria, Ethiopia, Egypt, DR Congo, Tanzania, Togo, Sierra Leone, Libya, Congo, Central African Republic, Liberia, Mauritania, Eritrea, Gambia, Seychelles, Zambia, Chad, Somalia, Senegal, Zimbabwe, Guinea, Rwanda, Uganda, Sudan, Algeria, Morocco, Angola, Ghana, Mozambique, Madagascar, Benin, Burundi. Medical Laboratory Instruments, Hospital Lab Instruments Equipments, Hospital Laboratory Instruments Tools, Medical Lab Instruments Tool Kits, Zoll PD 2000 Defibrillator Manufacturers, and Hospital Laboratory Instruments Suppliers from India, Zoll PD 2000 Defibrillator China, Zoll PD 2000 Defibrillator Kenya.

Zoll PD 2000 Defibrillator Tender Suppliers, Guadeloupe (Basse-Terre), Guatemala (Guatemala City), Guyana (Georgetown), Haiti (Port-au-Prince), Honduras (Tegucigalpa), Jamaica (Kingston), Martinique (Fort-de-France), Mexico (Mexico City), Montserrat (Brades), Nicaragua (Managua), Panama (Panama City), Paraguay (Asunción), Peru (Lima), Puerto Rico (San Juan), Saint Barthelemy (Gustavia), Trinidad and Tobago (Port-of-Spain), Turks and Caicos Islands (Cockburn Town), USA (Washington DC, America), Uruguay (Montevideo), Venezuela (Caracas), Virgin Islands (Charlotte Amalie), Anguilla (The Valley), Antigua and Barbuda (Saint Johns), Argentina (Buenos Aires), Aruba (Oranjestad), Bahamas (Nassau), Barbados (Bridgetown), Belize (Belmopan), Bermuda (Hamilton), Bolivia (Sucre), Brazil (Brasilia), British Virgin Islands (Road Town), Canada (Ottawa), Cayman Islands (George Town), Chile (Santiago), Colombia (Bogota), Costa Rica (San Jose), Cuba (Havana), Curacao (Willemstad), Dominica (Roseau), Zoll PD 2000 Defibrillator Tender Suppliers, Dominican Republic (Santo Domingo), Ecuador (Quito), El Salvador (San Salvador), Falkland Islands (Stanley), French Guiana (Cayenne), Greenland (Nuuk), Grenada (Saint Georges), Saint Kitts and Nevis (Basseterre), Saint Lucia (Castries), Saint Martin (Marigot), Saint Pierre and Miquelon (Saint-Pierre), Saint Vincent and the Grenadines

(Kingstown), Sint Maarten (Philipsburg), South Georgia and South Sandwich Islands (King Edward Point), Suriname (Paramaribo)

Technical Specification :

Zoll PD 2000 Defibrillator Innovative features: Large Monitor Non-fade monitor ECG monitor Strip recorder AC power supply for stationary use Specifications: Type: VVI demand; asynchronous (fixed rate) when used without ECG leads Pulse Type: Rectilinear, constant current Pulse Duration: 40 milliseconds. Pulse Amplitude: Variable to 140 mA Pacing Rate: Variable from 30 to 180 PPM Output Protection: Fully defibrillator-protected and isolated Pacer On: Message display on monitor Defibrillator Waveform: Damped sinusoid Output Energy Delivered: Selectable at 2, 3, 5, 7, 10, 20, 30, 50, 100, 150, 200, 300, 360 joules Charge Time: Less than 10 seconds Delivered Energy Display: CRT monitor displays delivered energy Synchronized Mode: Synchronizes defibrillator pulse to patient's R-wave. "SYNC" message displayed on monitor. Marker on monitor and on recorder paper identifies R-wave Internal Paddles: Output limited to 50 joules when internal paddles are connected. Discharge from paddles Charge Controls: Control on apex paddle and front panel. Paddles: Standard paddles are anterior/anterior adult and pediatric. Adult paddles slide off to expose pediatric paddles Defibrillation Electrodes: Specifically designed ZOLL Multi- Function Electrodes used in anterior/anterior or anterior/posterior positions; packaged in pairs Integral Defibrillator Tester: Integral circuitry allows complete test of defibrillator charge and discharge without removing paddles from storage wells. Identical circuitry allows complete test of unit configured with multifunction cable Defib On: Message display on monitor Monitor and Display Patient Connection: Via 3-lead ECG cable, paddles, and electrodes. Selectable by front panel switch Input Protection: Fully defibrillator-protected. Special circuit prevents distortion of ECG by pacer pulse Bandwidth: .5 – 40 Hz (-3dB) standard Display Format: Nonfade, moving trace with freeze capability Monitor On: Message display on monitor Screen Type: High-resolution CRT display Screen Size: 5 inches diagonally (108 mm x 85 mm viewing area) Zoll PD 2000 Defibrillator, Electrical Defibrillator exporters, Electrical Defibrillator manufacturers

NAUGRA[®]

Medical Hospital Equipments Manufacturers

Website:Medical Hospital Equipments Manufacturers,